


Close Up Rings



Model	Specification
KW-EXT1	1mm
KW-EXT5	5mm
KW-EXT10	10mm
KW-EXT20	20mm
LMZ4S	1mm, 5mm, 10mm, 20mm

Filter Holders



- An optional filter holder can be attached to the JC5MC series. (LM12JC5MC, LM16JC5MC and LM25JC5MC)

Model	Specification
FL-12JC5MC	Φ32
FL-16JC5MC	
FL-25JC5MC	

Mount Adapters



- VM series can change the flange back by using optional mount adapters included with each lens.
Standard: M42-mount has a 17.526mm flange back distance.

Series	Mount Adapter	Flange Back (mm)	Mount
VM42	FB-1600VM	16	M42 mount
	FB-1148VM	11.48	M42 mount
	FB-1000VM	10	M42 mount
	FB-0656VM	6.56	M42 mount
	FB-1750VM	17.5	TFL-II mount

*Mount adapters do not work with VM35 series lenses.

Field of View

FC24M series

LM8FC24M

WD mm	Magni- fication	Fields of View (mm)					
		1.1"		1"		2/3"	
		H	V	H	V	H	V
1000	0.009	1688.7	1269.1	1534.6	1147.5	1050.3	783.9
950	0.009	1605.1	1206.3	1458.6	1090.8	998.3	745.1
900	0.009	1520.6	1142.9	1381.9	1033.5	945.9	706.0
850	0.010	1436.3	1079.7	1305.3	976.3	893.6	667.0
800	0.011	1353.4	1017.3	1230.0	919.9	842.0	628.5
750	0.011	1270.5	955.0	1154.6	863.5	790.4	590.0
700	0.012	1187.5	892.6	1079.2	807.2	738.8	551.5
650	0.013	1104.0	829.9	1003.3	750.5	686.9	512.7
600	0.014	1020.6	767.2	927.5	693.8	635.0	474.0
550	0.015	937.7	704.9	852.2	637.4	583.5	435.5
500	0.017	854.9	642.6	776.9	581.1	531.9	397.0
450	0.019	772.1	580.3	701.6	524.8	480.4	358.6
400	0.021	689.2	518.0	626.3	468.4	428.8	320.1
350	0.024	606.2	455.6	550.9	412.0	377.1	281.5
300	0.027	523.2	393.3	475.5	355.6	325.5	243.0
250	0.033	440.3	330.9	400.1	299.2	273.9	204.5
200	0.040	357.2	268.5	324.6	242.8	222.2	165.9
150	0.052	273.9	205.9	248.9	186.2	170.5	127.3
100	0.075	190.1	143.0	172.8	129.4	118.5	88.5

LM16FC24M

WD mm	Magni- fication	Fields of View (mm)					
		1.1"		1"		2/3"	
		H	V	H	V	H	V
1000	0.016	905.7	677.6	820.7	612.8	561.2	419.9
950	0.017	861.1	644.2	780.4	582.7	533.6	399.3
900	0.017	816.6	610.9	740.0	552.6	506.0	378.6
850	0.019	772.1	577.6	699.7	522.4	478.4	358.0
800	0.020	727.5	544.3	659.3	492.3	450.8	337.3
750	0.021	683.0	511.0	618.9	462.2	423.2	316.7
700	0.022	638.4	477.7	578.6	432.0	395.6	296.0
650	0.024	593.9	444.3	538.2	401.9	368.0	275.4
600	0.026	549.4	411.0	497.8	371.7	340.4	254.7
550	0.028	504.8	377.7	457.5	341.6	312.8	234.1
500	0.031	460.3	344.3	417.1	311.4	285.2	213.4
450	0.034	415.7	311.0	376.7	281.3	257.6	192.7
400	0.038	371.1	277.7	336.3	251.1	230.0	172.1
350	0.044	326.6	244.3	295.9	221.0	202.4	151.4
300	0.051	282.0	211.0	255.5	190.8	174.7	130.8
250	0.060	237.4	177.6	215.1	160.6	147.1	110.1
200	0.074	192.8	144.2	174.7	130.5	119.5	89.4
150	0.096	148.1	110.8	134.2	100.2	91.8	68.7
100	0.138	103.3	77.3	93.6	69.9	64.0	47.9

LM35FC24M

WD mm	Magni- fication	Fields of View (mm)					
		1.1"		1"		2/3"	
		H	V	H	V	H	V
1000	0.035	399.0	300.0	362.2	271.7	249.1	186.8
950	0.037	379.3	285.2	344.4	258.3	236.8	177.6
900	0.039	359.7	270.4	326.5	244.9	224.5	168.4
850	0.042	340.0	255.7	308.7	231.6	212.3	159.2
800	0.044	320.4	240.9	290.9	218.2	200.0	150.0
750	0.047	300.8	226.1	273.0	204.8	187.7	140.8
700	0.050	281.1	211.4	255.2	191.4	175.5	131.6
650	0.054	261.5	196.6	237.4	178.0	163.2	122.4
600	0.058	241.8	181.8	219.5	164.6	150.9	113.2
550	0.064	222.1	167.0	201.7	151.3	138.6	104.0
500	0.070	202.4	152.2	183.8	137.8	126.4	94.8
450	0.077	182.7	137.4	165.9	124.4	114.1	85.5
400	0.087	163.0	122.5	148.0	111.0	101.7	76.3
350	0.099	143.2	107.7	130.0	97.5	89.4	67.0
300	0.114	123.4	92.8	112.0	84.0	77.0	57.8
250	0.136	103.5	77.8	93.9	70.4	64.6	48.4
200	0.169	83.4	62.7	75.7	56.8	52.0	39.0

LM6FC24M

WD mm	Magni- fication	Fields of View (mm)					
		1.1"		1"		2/3"	
		H	V	H	V	H	V
1000	0.007	2252.1	1669.3	2033.1	1506.4	1377.1	1026.1
950	0.007	2141.3	1587.1	1933.1	1432.3	1309.4	975.6
900	0.007	2030.4	1505.0	1833.0	1358.1	1241.6	925.1
850	0.008	1919.6	1422.9	1732.9	1284.0	1173.8	874.6
800	0.008	1808.7	1340.7	1632.9	1209.9	1106.1	824.1
750	0.009	1697.9	1258.6	1532.8	1135.8	1038.3	773.6
700	0.009	1587.0	1176.4	1432.8	1061.6	970.5	723.1
650	0.010	1476.2	1094.3	1332.7	987.5	902.8	672.6
600	0.011	1365.3	1012.1	1232.6	913.4	835.0	622.1
550	0.012	1254.5	930.0	1132.6	839.2	767.2	571.6
500	0.013	1143.6	847.8	1032.5	765.1	699.4	521.1
450	0.014	1032.7	765.6	932.4	691.0	631.7	470.6
400	0.016	921.9	683.5	832.3	616.8	563.9	420.1
350	0.018	811.0	601.3	732.3	542.7	496.1	369.6
300	0.021	700.1	519.2	632.2	468.5	428.3	319.1
250	0.025	589.2	437.0	532.1	394.4	360.5	268.6
200	0.031	478.2	354.8	431.9	320.2	292.7	218.1
150	0.040	367.2	272.6	331.8	246.0	224.9	167.6
100	0.057	255.8	190.1	231.2	171.6	156.9	117.0

LM12FC24M

WD mm	Magni- fication	Fields of View (mm)					
		1.1"		1"		2/3"	
		H	V	H	V	H	V
1000	0.012	1174.7	883.2	1067.1	799.4	732.2	548.0
950	0.013	1117.0	839.8	1014.7	760.1	696.2	521.1
900	0.013	1059.3	796.4	962.3	720.8	660.3	494.1
850	0.014	1001.6	753.0	909.8	681.5	624.3	467.2
800	0.015	943.9	709.6	857.4	642.2	588.3	440.2
750	0.016	886.2	666.2	805.0	603.0	552.3	413.3
700	0.017	828.5	622.8	752.6	563.7	516.3	386.4
650	0.018	770.8	579.4	700.2	524.4	480.3	359.5
600	0.020	713.1	536.0	647.7	485.1	444.3	332.5
550	0.022	655.4	492.6	595.3	445.8	408.4	305.6
500	0.024	597.7	449.2	542.9	406.5	372.4	278.6
450	0.026	540.0	405.8	490.4	367.2	336.4	251.7
400	0.030	482.3	362.4	438.0	327.9	300.4	224.8
350	0.034	424.6	319.0	385.5	288.6	264.4	197.8
300	0.039	366.8	275.5	333.1	249.3	228.4	170.9
250	0.046	309.1	232.1	280.6	210.0	192.3	143.9
200	0.057	251.3	188.6	228.1	170.7	156.3	116.9
150	0.074	193.4	145.1	175.5	131.3	120.2	89.9
100	0.106	135.3	101.4	122.8	91.8	84.0	62.8

LM25FC24M

WD mm	Magni- fication	Fields of View (mm)					
		1.1"		1"		2/3"	
		H	V	H	V	H	V
1000	0.025	576.2	431.8	522.5	390.8	358.0	268.2
950	0.026	547.8	410.6	496.7	371.5	340.4	255.0
900	0.027	519.5	389.3	471.0	352.3	322.8	241.8
850	0.029	491.1	368.0	445.3	333.1	305.1	228.6
800	0.031	462.7	346.8	419.6	313.8	287.5	215.4
750	0.033	434.4	325.5	393.8	294.6	269.9	202.2
700	0.035	406.0	304.2	368.1	275.3	252.2	188.9
650	0.038	377.6	283.0	342.4	256.1	234.6	175.7
600	0.041	349.2	261.7	316.6	236.8	216.9	162.5
550	0.044	320.9	240.4	290.9	217.5	199.3	149.3
500	0.049	292.5	219.1	265.2	198.3	181.7	136.1
450	0.054	264.1	197.9	239.4	179.0	164.0	122.9
400	0.060	235.7	176.6	213.7	159.8	146.4	109.6
350	0.069	207.3	155.3	187.9	140.5	128.7	96.4
300	0.079	178.9	134.0	162.2	121.2	111.1	83.2
250	0.094	150.5	112.7	136.4	102.0	93.4	69.9
200	0.117	122.1	91.4	110.6	82.7	75.7	56.7
150	0.152	93.6	70.0	84.8	63.3	58.0	43.