




ø16 1.8/16mm C		
FOCAL LENGTH		f=16mm
MAX. DIAMETER (RATIO)		F=1:1.8~22
ELEMENT		9 GROUPS 11 ELEMENTS
PICTURE SIZE		12.8x9.6mm
ANGLE	VER. ANGLE	33.6°
	HOR. ANGLE	44.0°
	DIA. ANGLE	53.8°
DISTORTION (TV)		0.02%
SHOOTING RANGE AT	VER.	69.9 mm
MINIMUM FOCUS	HOR.	93.5 mm
DISTANCE	DIA.	117 mm
MINIMUM FOCUS DISTANCE		0.1m
FLANGE BACK		17.526mm in air
BACK FOCUS		13.0mm in air
FILTER SCREW SIZE		M34x0.5
FRONT/REAR EFFECTIVE DIA.		FRONT ø27mm REAR ø16.5mm
MOUNT		C-MOUNT
EXIT PUPIL		-26.2mm
TEMPERATURE RANGE		-10~+50° C
STORAGE TEMPERATURE RANGE		-20~+60° C
RESOLUTION CENTER/CORNER		CENTER 160L/mm CORNER 120L/mm
LENS COATING		WIDE BAND MULTI COATING
WEIGHT		g

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺 度	1/1	承 認	八木	製 図	大口
		LM16SC					
		1" F1.8 f=16mm					
2013.5.8	作成年月日						